



THE ROUTE OF LEAST RESISTANCE

HEAR NO EVIL

VAN DAMME PRO GRADE CLASSIC XKE PRO-PATCH CABLE



Van Damme Pro Grade Classic XKE Pro-patch cable has been specifically designed as a 4.85mm overall diameter cable to suit Neutrik and Switchcraft bantam jacks, and other applications requiring a lower OD cable. Its braided screen and tightly packed construction ensure that the smaller size in no way compromises the mechanical and sonic integrity.

KEY BENEFITS



Multiple Colours



Flexibility



Reduced Overall Diameter

MATERIALS



Oxygen Free Copper



Flexible PVC



Cross-linked polyethylene



Silver-plated oxygen-free copper

APPLICATIONS



Broadcast



Presentations



Live Sound

www.van-damme.com

HEAR NO EVIL

Applications

- For mic and line level analogue balanced audio
- Bantam patch cords and bantam adaptor cables
- Shorter mic cables and XLR splitter cables
- Midi leads and other DIN connector applications

Application Notes

- Further improved outer jacket ensures cable remains flexible in sub-zero temperatures
- Tightly packed cotton fillers ensure no static build up and even capacitance
- Available in 10 colours for application or length colour coding
- 95% optical coverage braided screen for excellent mechanical strength and EMI/RFI rejection
- Combination of silver plated and plain ultra-pure oxygen free copper conductors for unsurpassed sound quality

Mechanical Specification

Conductors	7 x 0.10 mm silver plated ultra-pure oxygen-free copper 21 x 0.10 mm bare ultra-pure oxygen-free copper
Conductor size	28 x 0.10 mm, 0.22 mm ² , AWG 24/28
Insulation	Cross-linked polyethylene (XLPE)
Insulation diameter	1.60 ± 0.10 mm
Colour Code	Red/Blue
Screen	96 x 0.10 mm braided tinned copper > 95% optical coverage
Jacket material	Flexible PVC/Neoprene composite
Overall diameter	4.85 ± 0.15 mm
Bend radius	10 x overall diameter
Operating temperature	-20 to +70 °C

Electrical Specification

Resistance	Conductor	< 85 Ohm/km
	Insulation	> 5000 MOhm/km
Capacitance	Core to core	50 pF/m
	Core to screen	95 pF/m



HEAR NO EVIL

Part Numbers and Description

Part Number	Description	RAL Code	Max. Reel Length
268-006-000	Van Damme Tour Grade XKE Pro-Patch jet black	RAL 9005	100 m
268-007-060	Van Damme Tour Grade XKE Pro-Patch ultramarine blue	RAL 5002	100 m
268-009-020	Van Damme Tour Grade XKE Pro-Patch traffic red	RAL 3020	100 m
268-004-050	Van Damme Tour Grade XKE Pro-Patch mint green	RAL 6029	100 m
268-018-080	Van Damme Tour Grade XKE Pro-Patch squirrel grey	RAL 7000	100 m
268-010-040	Van Damme Tour Grade XKE Pro-Patch sulphur yellow	RAL 1016	100 m
268-056-090	Van Damme Tour Grade XKE Pro-Patch traffic white	RAL 9016	100 m
268-058-030	Van Damme Tour Grade XKE Pro-Patch bright orange	RAL 2007	100 m
268-060-010	Van Damme Tour Grade XKE Pro-Patch nut brown	RAL 8011	100 m
268-062-070	Van Damme Tour Grade XKE Pro-Patch signal violet	RAL 4008	100 m

Standards and Compliance

RoHS 2011/65/EU Restriction of Hazardous Substances

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals