

HEAR NO EVIL

VAN DAMME BLACK SERIES TOUR GRADE MULTICORE SPEAKER CABLE



Van Damme Black Series Tour Grade Multicore Speaker Cable offers a comprehensive range of core counts and conductor sizes, covering most low impedance speaker systems. In addition, the 18 core 1.50 mm² and 2.50 mm² multicores are rated for use with mains voltage for lighting dimmer to fixture 19 pole assemblies.

KEY BENEFITS



Multiple Options



Flexibility

MATERIALS



Oxygen Free Copper



Flexible PVC

APPLICATIONS



Presentations



Live Sound



Lighting

HEAR NO EVIL

Applications

- Matt black jacket for on stage use
- 1.50 mm² and 2.50 mm² 18 core multicores **only** for lighting power
- 4.00 mm² conductors for professional line array and point source sound reinforcement

Application Notes

- Wide range of conductor counts & sizes
- Optimised for dynamic use
- 16 and 24 x 4.00 mm² are for speaker applications only
- 18 and 16 core cables use a colour code for easy termination
- Ultra-pure oxygen free copper for outstanding sonic integrity

General Specification

Conductor	Bare ultra-pure oxygen free copper
Insulation	PVC
Jacket	Flexible PVC composite Jet Black RAL 9005
Bend Radius	10 x overall diameter
Operating temperature	Static -20 to +70 °C
	Flexing -10 to +70 °C

Characteristics by part number

Part Number	Conductor Size	Overall Diameter (mm)	Stranding	Resistance Ohm/km
268-542-000	2.50 mm ²	10.25	50 x 0.25 mm	7.65
268-562-000	2.50 mm ²	11.60	50 x 0.25 mm	7.65
268-582-000	2.50 mm ²	15.80	50 x 0.25 mm	7.65
268-544-000	4.00 mm ²	12.20	127 x 0.20 mm	4.60
268-584-000	4.00 mm ²	17.70	127 x 0.20 mm	4.60
268-515-018	1.50 mm ²	14.50	30 x 0.25 mm	12.30
268-525-018	2.50 mm ²	18.00	50 x 0.25 mm	7.65
268-545-016	4.00 mm ²	23.80	127 x 0.20 mm	4.60
268-545-024	4.00 mm ²	27.80	127 x 0.20 mm	4.60

Cable colour codes

2 to 8 Conductor:

Conductor 1	Red
Conductor 2	Blue
Conductor 3	Green
Conductor 4	Yellow
Conductor 5	White
Conductor 6	Black
Conductor 7	Brown
Conductor 8	Violet

HEAR NO EVIL

16 and 18 Conductor:

Conductor 1	Red	Conductor 10	Orange
Conductor 2	Grey	Conductor 11	Pink
Conductor 3	Brown	Conductor 12	Purple
Conductor 4	Blue	Conductor 13	Red/white
Conductor 5	Black	Conductor 14	Purple/white
Conductor 6	White	Conductor 15	Black/white
Conductor 7	Green/yellow	Conductor 16	Blue/white
Conductor 8	Cream	Conductor 17	Brown/white
Conductor 9	Clear	Conductor 18	Grey/white

24 Conductor:

Red and Blue pairs; numbered 1 to 12

Part Numbers and Description

Part Number	Description	Max. Reel Length
268-542-000	Van Damme Black Series Tour Grade 4 x 2.50 mm ² multicore	500 m
268-562-000	Van Damme Black Series Tour Grade 6 x 2.50 mm ² multicore	500 m
268-582-000	Van Damme Black Series Tour Grade 8 x 2.50 mm ² multicore	500 m
268-544-000	Van Damme Black Series Tour Grade 4 x 4.00 mm ² multicore	500 m
268-584-000	Van Damme Black Series Tour Grade 8 x 4.00 mm ² multicore	500 m
268-515-018	Van Damme Black Series Tour Grade 18 x 1.50 mm ² multicore	500 m
268-525-018	Van Damme Black Series Tour Grade 18 x 2.50 mm ² multicore	500 m
268-545-016	Van Damme Black Series Tour Grade 16 x 4.00 mm ² multicore	300 m
268-545-024	Van Damme Black Series Tour Grade 24 x 4.00 mm ² multicore	200 m

Standards and Compliance

RoHS 2011/65/EU Restriction of Hazardous Substances

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals